

COOLANT FLUSH-N-FILL

COOLING RADIATOR FLUSH AND EXCHANGER MACHINE

MODEL - PRX-3000



- It cleans and replaces worn out coolant liquid of Cars, SUV and Lorries.
- Technician friendly easy to use.
- See-thru storage tubes allow visual comparison of old and new coolants

CERAMIC FILTER



KIT HOSES & COUPLINGS

TECHNICAL SPECIFICATIONS

Power Supply	Automatic battery 12V DC
Max Functioning Pressure	5/7bar 85/100psi
Tank	2 Nos. (for new and old fluids)
Tank Capacity	30 Ltrs. Per Tank
Oil Inlet and Return Hoses	3-(2x) 126 (L) x 1/2(dia.) inches (1-red, 1-black) (1) 137(L) x1/2(dia.) inches (red) ; All with male and female quick couplers, 300PSL (max.) rated
Pressure Regulator	Manual control dial, locking, 1-1/2 inches
Pressure Gauges	Both 2-3/4 (dia.) inches, 0~100 PSI, 20 PSI increments, 0~7 Bar, in 1 and 1/10 Bar increments

* Specifications subject to change without notice

PRECISION TESTING MACHINES PVT. LTD.

HEAD OFFICE: S-12, Okhla Industrial Area, Phase - II, New Delhi - 110 020 (India)

Tel.: 011-4161-0000 (4 lines), 2638-6612 Fax: 011-26383790

E-mail : sales@precisionworld.net / service@precisionworld.net / www.precisionworld.net